



Clamp Meters



Figure 1 Model shown GPS-212

GPS-212 AC Auto-Ranging Clamp Meter

GPS-275 AC/DC Auto-Ranging T-RMS Clamp Meter

Confidently take reliable readings with the GPS-212/GPS-275 clamp meters. The extra wide jaw easily clamps around large conductors, typically found in high current applications. The rugged design CAT-IV 600V, CAT-III 1000V ratings add an extra element of protection when taking high-powered measurements. The measurement of capacitance, temperature (not available in GPS-212), resistance and frequency makes this a most versatile tool for utilities, electrical contractors and industrial service technicians.

Key Features

- Large backlit display of 3999 counts
- T-RMS measurements (GPS-275) for AC Voltage and AC Current
- Built-in non-contact voltage detector
- Electronic Overload Protection
- Auto Power Off & Data Hold
- Low battery indicator
- 52mm clamp jaw opening size
- PEAK Hold function (GPS-275)
- With soft carrying case

Ideal for

- Outdoor measuring
- Circuit measurements
- Wind power, PV power and other renewable energy equipment
- Automotive electronics/electric car testing
- Electric power systems
- Industrial scenarios of electric debug testing and measuring
- Education and science research
- Plant automation systems
- HVAC and process control

Technical Specifications

Model	GPS-212	GPS-275
Digital Display Counts	4000	4000
Display with Backlight	YES	YES
True-RMS Measurements	NO	YES
Data Hold function	YES	YES
Electronic Overload Protection	YES	YES
Max. Hold function	NO	YES
Zero Function for DC current	----	YES
PEAK Hold function	NO	YES
Low battery indication	YES	YES
Auto Power off function	YES	YES
Analogue Bar graph	NO	YES
Non-contact Voltage Detection	YES	YES
AC/DC Current measurement	AC	AC/DC
Jaw size	2" (52mm)	2" (52mm)
DC Current /Resolution/ Accuracy	----	1000A / 0.01A/2.8%
AC Current /Resolution/ Accuracy	1000A / 0.01A/0.8%	1000A / 0.01A/2.8%
DC Voltage / Resolution / Accuracy	1000V / 0.1mV / ±0.8%	600V / 0.1mV / ±0.8%
AC Voltage / Resolution / Accuracy	1000V / 1mV / ±1.5%	600V / 0.1mV / ±1.0%
Resistance / Resolution / Accuracy	40MΩ / 0.1Ω /±1.0%	40MΩ / 0.1Ω /±1.0%
Capacitance / Resolution	100μF / 0.01nF	40mF / 0.001nF
Frequency / Resolution	9.99 MHz/0.001Hz	4KHz/0.001Khz
Duty cycle	0.1 to 99.0 %	0.1 to 99.0 %
Diode check/ Continuity test	YES/YES	YES/YES
Temperature measurement	----	-20 to 760°C

Standard Accessories

Test leads
 9V Battery
 Temperature probe (GPS-275 only)
 Soft carrying case
 User manual



General Specifications

Part Numbers / Optional Accessories		
Code	Item	Part Number
GPS-212	AC Auto-ranging Clamp Meter	460212
GPS-275	AC/DC Auto-ranging True-RMS Clamp Meter	464275

Dimensions

271 x 100 x 35mm / 10.5 x 4 x 1.8" (w x d x h) approx.

Mass

0.5kg/1.1lbs approx.

Services

1-year warranty (subject to product registration with GPS Ltd)

Visit www.gpslimited.com/register-product

Service and calibration available.

Please contact for more information

www.gpslimited.com/ClampMeter
 For all enquiries, Tel: +44 (0) 208 964 3600
 Email: info@gpslimited.com